

according to Regulation (EC) No 1907/2006 (REACH) as amended

**BALTECH S6005 THINNER**

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- 1.1. Product identifier**  
BALTECH S6005 THINNER  
Substance / mixture substance  
Number EC: 905-588-0  
Chemical name reaction mass of ethylbenzene and xylene  
EC (EINECS) number 905-588-0  
Registration number 01-2119539452-40  
Other substance name  
Ředidlo pro nátěrové hmoty syntetické.
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Substance's intended use**  
Diluent. Solvent.  
**Substance uses advised against**  
not available
- 1.3. Details of the supplier of the safety data sheet**  
**Distributor**  
Name or trade name BARVY A LAKY TELURIA,s.r.o.  
Address č.p.1, Skrchov, 679 61  
Czech Republic  
Identification number (CRN) 43420371  
VAT Reg No CZ43420371  
Phone +420 516 474 211  
E-mail tel@teluria.cz  
Web address http://www.bal.cz
- Competent person responsible for the safety data sheet**  
Name BARVY A LAKY TELURIA,s.r.o.  
E-mail tel@teluria.cz
- 1.4. Emergency telephone number**  
European emergency number: 112

**SECTION 2: Hazards identification**

- 2.1. Classification of the substance or mixture**  
**Classification of the substance in accordance with Regulation (EC) No 1272/2008**  
The substance is classified as dangerous.

Flam. Liq. 3, H226  
Asp. Tox. 1, H304  
Acute Tox. 4, H312+H332  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
STOT SE 3, H335  
STOT RE 2, H373

Full text of all classifications and hazard statements is given in the section 16.

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### Most serious adverse physico-chemical effects

Flammable liquid and vapour.

### Most serious adverse effects on human health and the environment

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Harmful in contact with skin or if inhaled.

## 2.2. Label elements

### Hazard pictogram



### Signal word

Danger

### Dangerous substance

reaction mass of ethylbenzene and xylene  
(EC: 905-588-0)

### Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H312+H332	Harmful in contact with skin or if inhaled.

### Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P310	Immediately call a doctor.
P501	Dispose of contents/container to in accordance with local regulations by handing over to a person authorized to dispose of waste or a site designated by the town.

### Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

## 2.3. Other hazards

Substance does not meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Vapours have intoxicating and narcotic effect, causing headaches, eye irritation and respiratory tract irritation. If swallowed may cause lungs injury (aspiration bronchopneumonia).

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

##### Chemical characterization

Multi-component substance: &gt;72 % xylene (72-83 %) and &lt;25 % ethylbenzene (17-25 %).

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
EC: 905-588-0 Registration number: 01-2119539452-40	<b>substance main component</b> reaction mass of ethylbenzene and xylene	>97	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373	1, 2

##### Notes

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 Substance with a Union workplace exposure limit.

Full text of all classifications and hazard statements is given in the section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

##### If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

##### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

##### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

##### If swallowed

DO NOT INDUCE VOMITING - even the inducing of vomiting by itself may cause complications (i.e. inhalation of the substance in airways and lungs or mechanical damage to the mucous membrane of the pharynx may pose a higher threat than the ingested substance in this case). If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

Cough, headache. May cause respiratory irritation.

#### If on skin

Causes skin irritation.

#### If in eyes

Causes serious eye irritation.

#### If swallowed

Irritation, nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment. Pay attention: contains organic solvents. Ingestion or vomiting may occur due to aspiration into the lungs and then a rapid absorption and damage to other organs. In case of suspected break-liquid ingredients into the lungs get medical help immediately. Get medical supervision for at least 48 hours after ingestion of liquid. If you see a doctor, take this safety data sheet with you.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

#### Unsuitable extinguishing media

Water - full jet.

### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For workers apart from emergency teams: Avoid inhalation of vapour, prevent skin and eye contact. Wear appropriate protective clothing and gloves. Wear eye protection and face shield if necessary. Use suitable respiratory protection. In closed spaces, ensure fresh air supply. Eliminate all ignition sources. No smoking and no open fire. Keep unnecessary personnel away.

For members of emergency teams: Use appropriate personal protective equipment – protective clothing with antistatic finish and impermeable work shoes. Treat unprotected skin with barrier cream. Anti-chemical protective gloves. For short-time exposure or low concentration, use respirator with organic vapour and dust filter (protection level A/P2); for high concentration and long-term exposure, self-contained respirator is necessary.

### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water. If possible prevent leakage, close container and place damaged container in protective container.

Spill: Prevent further leakage or spillage if safe to do so. Do not allow to enter drains, basements or confined areas.

Leakage: Prevent further leakage or spillage if safe to do so. If the leak contaminates a river, lake or sewer, inform the relevant authorities. Prevent contamination of the soil and entering surface or ground water. If possible prevent leakage, close container and place damaged container in protective container.

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

### 6.4. Reference to other sections

See the Section 7, 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### 7.1.1. General health measures

Use the product after due familiarization with its hazard characteristics and proper training or training in its safe use. Do not eat, drink, smoke on the site. Wash your hands and other contaminated parts of body by soap and water before eating and after the use of product is finished. Abide by requirements on personal hygiene when working with hazardous chemical products.

Use technical equipment on the site to control human and environment exposure. Regularly inspect the equipment, ensure cleaning, timely maintenance and permanent functionality. When working, use the recommended personal protective equipment listed in 8.2 of the Safety Data Sheet and in Annex to the Safety Data Sheet. Keep the protective clothing and protective equipment sound and clean. Immediately replace the damaged protective aids for sound ones. Keep the site, tools and aids clean and in sound state. On the site, keep the product in labelled containers or tanks. Store product waste and wastes contaminated by the product in suitable and properly labelled vessels located on designated marked and protected places. Ensure long-term storing of wastes containing the product outside the site.

#### 7.1.2. Fire precautions

When using the product, prevent potential ignition or explosion of the mixture of product vapour and air caused by contact with open flame, sparks, extremely hot surfaces, electrostatic discharges. Do not smoke on the site, use non-sparking tools. Places with increased occurrence of the vapour-air mixture need to be ventilated to prevent formation of explosive mixtures. Solvent vapours are heavier than air. The site should be protected from electrostatic discharges.

#### 7.1.3. Environmental precautions

Handle the product on a site technically adapted to avoid accidental leakage to sewerage systems, water or soil. Product waste and wastes contaminated by the product to be disposed of as hazardous waste. Waste water contaminated by the product may only be discharged to water reservoirs after the product components are properly removed in a waste water treatment plant or in other appropriate treatment plant able to remove drifted product components from water. Do not pour the product to waste water. Emissions of solvent from point sources are subjected to control requirements acc. to air protection regulations.

### 7.2. Conditions for safe storage, including any incompatibilities

Store the product in properly marked, closed containers in well ventilated spaces at 5 – 25 °C. The storages must meet the requirements on storing of flammable liquids and substances hazardous for aquatic life and soil. Protect from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Store away from oxidising substances and strong acids. Do not store with food, drinks, feed material, medicines. Storages should be protected from static electricity. First aid kit and water suitable for eye rinsing should be available. Keep away from products that are corrosive to metals (eg acids or pool chemicals).

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

Content	Packaging type	Material of package
0,4 l	can / tin	FE
0,7 l	can / tin	FE
4 l	jerry can	FE
9 l	jerry can	FE
160 kg	barrel / drum	FE
0,4 l	bottle	PET
0,7 l	bottle	PET

Storage class 3A - Flammable liquids (flash point below 55 °C)  
 Storage temperature min 5 °C, max 25 °C

### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

### 7.3. Specific end use(s)

The conclusions of the chemical safety assessment of a substance for use as a solvent, as a paint thinner and as a cleaning agent are incorporated in the relevant sections of the safety data sheet. Specific requirements for the safe industrial and professional use of the thinner from the point of view of worker protection and environmental protection, developed on the basis of information from exposure scenarios for the given types of use, are given in the annex to the safety data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### European Union

#### Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
xylenes	OEL 8 hours	221 mg/m <sup>3</sup>	Skin
	OEL 8 hours	50 ppm	
	OEL 15 minutes	442 mg/m <sup>3</sup>	
	OEL 15 minutes	100 ppm	
ethylbenzene	OEL 8 hours	442 mg/m <sup>3</sup>	Skin
	OEL 8 hours	100 ppm	
	OEL 15 minutes	884 mg/m <sup>3</sup>	
	OEL 15 minutes	200 ppm	

#### DNEL

according to Regulation (EC) No 1907/2006 (REACH) as amended

### BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

reaction mass of ethylbenzene and xylene

Workers / consumers	Route of exposure	Value	Effect	Determining method
Workers	Inhalation	221 mg/m <sup>3</sup>	Systemic chronic effects	
Workers	Inhalation	221 mg/m <sup>3</sup>	Local chronic effects	
Workers	Inhalation	442 mg/m <sup>3</sup>	Local acute effects	
Workers	Dermal	212 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	65.3 mg/m <sup>3</sup>	Systemic chronic effects	
Consumers	Inhalation	260 mg/m <sup>3</sup>	Systemic acute effects	
Consumers	Dermal	125 mg/kg bw/day	Systemic chronic effects	
Consumers	Oral	12.5 mg/kg bw/day	Systemic chronic effects	
Workers	Inhalation	221 mg/m <sup>3</sup>	Local chronic effects	
Workers	Inhalation	442 mg/m <sup>3</sup>	Systemic acute effects	
Consumers	Inhalation	65.3 mg/m <sup>3</sup>	Local chronic effects	
Consumers	Inhalation	260 mg/m <sup>3</sup>	Local chronic effects	

**PNEC**

reaction mass of ethylbenzene and xylene

Route of exposure	Value	Determining method
Freshwater environment	327 µg/l	
Seawater	327 µg/l	
Microorganisms in wastewater treatment plants	6.58 mg/l	
Freshwater sediment	12.46 mg/kg of dry substance of sediment	
Sea sediments	12.46 mg/kg of dry substance of sediment	
Soil (agricultural)	2.31 mg/kg of dry substance of soil	

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### 8.2. Exposure controls

Conditions of safe use of the registered product composition components specified in exposure scenarios to Safety Data Sheets of the components are given in Annex of the SDS, including the required additional measures restricting the exposure – see the exposure scenarios for the intended uses of the product.

General safety and hygienic measures. When working, do not eat, drink, smoke. Before the break and after the work, hands should be washed with soap and hot water, treated with barrier cream. Overall and local ventilation, effective extraction.

#### Eye/face protection

Protective goggles (closed eye protection) resistant to organic solvent or face shield.

#### Skin protection

Skin protection: Protective clothes with antistatic finish, protective shoes; treat unprotected skin with barrier cream. Hand protection: Chemical resistant protective gloves (EN 374-1:2003). Suitable material – fluoroelastomere and others, time of penetration corresponding to > 480 minutes. The time of penetration specified by the manufacturer should be followed and the glove replaced after expiration. If damaged, the gloves should be replaced immediately. The selection of suitable protective gloves does not only depend on their material, but also on other qualitative features. Furthermore, since the mixture can be used for various purposes, mixed with other substances, the suitability of gloves for all purposes cannot be predetermined and must be verified in particular use.

#### Respiratory protection

Don't breathe vapours. For short-time exposure or low concentration, use respirator with organic vapour and dust filter (protection level A/P2); for high concentration and long-term exposure, self-contained respirator is necessary.

#### Thermal hazard

Not available.

#### Environmental exposure controls

Ensure that containers are properly closed during storage, handling and transport. Secure storage areas against possible leakage of product into the environment (sewerage, water, soil - see 6.2). Do not flush product into drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-94,96 - 13,2 °C
Boiling point or initial boiling point and boiling range	136,2-144,5 °C
Flammability	inflammable
Lower and upper explosion limit	
bottom	6,7-7 %
upper	0,8-1,1 %
Flash point	18-23 °C
Auto-ignition temperature	432-528 °C
Decomposition temperature	not applicable
pH	data not available
Kinematic viscosity	data not available
Solubility in water	146-190,7 mg/l / 25 °C
Partition coefficient n-octanol/water (log value)	3,12-3,2
Vapour pressure	data not available
Density and/or relative density	
Density	0,862 g/cm <sup>3</sup> at 20 °C
Relative vapour density	data not available
Particle characteristics	data not available



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

Form

### 9.2. Other information

 Total organic carbon (TOC) 0,91 kg/kg

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The substance is flammable. The substance reacts with strong oxidizing agents.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No known dangerous reactions when used under standard conditions. Flammable liquid. Vapours may form explosive mixture with air. Vapours are heavier than air, accumulate near the ground and below ground, and the fire can spread over long distances.

### 10.4. Conditions to avoid

Thermal decomposition. The product is stable and no degradation occurs under normal use. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the substance.

#### Acute toxicity

Harmful in contact with skin or if inhaled.

reaction mass of ethylbenzene and xylene

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD <sub>50</sub>	3523 mg/kg bw		Rat (Rattus norvegicus)	M
Inhalation	LC <sub>50</sub>	29000 mg/m <sup>3</sup>		Rat (Rattus norvegicus)	
Dermal	LD <sub>50</sub>	12126 mg/kg bw		Rabbit	M

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

 Causes serious eye irritation. (Xylene is not classified as irritating to eyes according to CLP Regulation No. 1272/2008. However, mild eye irritation has been reported in volunteer studies in which individuals were exposed to 442 mg / m<sup>3</sup> xylene for 15-30 minutes.)

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

### Germ cell mutagenicity

Based on available data the classification criteria are not met.

### Carcinogenicity

Based on available data the classification criteria are not met.

### Reproductive toxicity

Based on available data the classification criteria are not met.

### Toxicity for specific target organ - single exposure

May cause respiratory irritation.

### Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

not available

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Acute toxicity

Acute aquatic ecotoxicity data are not available for any of the currents in this category. However, a complete acute dataset is available for each of the xylene and ethylbenzene isomers. As the isomers of xylene and ethylbenzene are the main components in this category, the "read across" method was used to obtain the data.

reaction mass of ethylbenzene and xylene

Parameter	Value	Time of exposure	Species	Environment
LC <sub>50</sub>	2.6 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	
EC <sub>50</sub>	1 mg/l	48 hour	Daphnia (Daphnia magna)	
EC <sub>50</sub>	2.2 mg/l	72 hour	Algae (Selenastrum capricornutum)	

### 12.2. Persistence and degradability

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### Biodegradability

reaction mass of ethylbenzene and xylene

Parameter	Value	Time of exposure	Environment	Result
				Easily biodegradable

Biotic:

Readily biodegradable: Expected to be readily biodegradable.

Abiotic:

Hydrolysis as a function of pH: Not expected to undergo hydrolysis. Photolysis: Photolysis is not expected to occur.

### 12.3. Bioaccumulative potential

reaction mass of ethylbenzene and xylene

Parameter	Value	Time of exposure	Species	Environment	Surrounding temperature [°C]
BCF	25.9				

It is not bioaccumulative.

### 12.4. Mobility in soil

 Adsorption to soil or sediment is not expected due to low  $\log K_o / v < 3$ .

### 12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

### 12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms as it does not meet the criteria set out in section B of Regulation (EU) No 2017/2100.

### 12.7. Other adverse effects

Harms public health and the environment by destroying ozone in the upper atmosphere. Contains substances known to be hazardous to the environment or not degradable in wastewater treatment plants.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### Waste type code

07 01 08 other still bottoms and reaction residues \*

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### Packaging waste type code

15 01 02 plastic packaging

15 01 04 metallic packaging

(\* ) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1307

### 14.2. UN proper shipping name

XYLENES

### 14.3. Transport hazard class(es)

3 Flammable liquids

### 14.4. Packing group

III - substances presenting low danger

### 14.5. Environmental hazards

not relevant

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

#### Additional information

Hazard identification No.

30

UN number

1307

Classification code

F1

Safety signs

3



### Air transport - ICAO/IATA

Packaging instructions passenger 355

Cargo packaging instructions 366

### Marine transport - IMDG

EmS (emergency plan) F-E, S-D

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

### 15.2. Chemical safety assessment

The relevant exposure scenarios are incorporated in the annex to the safety data sheet.

### SECTION 16: Other information

#### A list of standard risk phrases used in the safety data sheet

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H312+H332	Harmful in contact with skin or if inhaled.

#### Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P501	Dispose of contents/container to in accordance with local regulations by handing over to a person authorized to dispose of waste or a site designated by the town.
P261	Avoid breathing vapours.
P280	Wear protective gloves/eye protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P310	Immediately call a doctor.

#### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

#### Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC <sub>50</sub>	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
ES	Identification code for each substance listed in EINECS
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BALTECH S6005 THINNER

Creation date	06th February 2017	Version	2.0
Revision date	07th December 2021		

LC <sub>50</sub>	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD <sub>50</sub>	Lethal dose of a substance in which it can be expected death of 50% of the population
log K <sub>ow</sub>	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution from Ships
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

Commission Regulation (EU) 2020/878 of 18 June 2020. REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

Version 2.0 replaces version of 06.02.2017. Overall revision of SDS in accordance with Commission Regulation (EU) 2020/878.

### More information

Classification procedure - calculation method.

### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.