

Page number: 01



Composition Mixture of pigments and fillers in solution of aldehyde resin in organic solvents.

Characteristics and use Universal tinting concentrate, which is compatible almost with most paints on various basis (synthetic air-drying paints, baking paints, polyurethane paints, epoxide paints). It is recommended to use only in tinting system HOSTEMIX.

Shades
 13 basic shade concentrates
 2 filler concentrates (for alkyd and polyurethane paints)
 1 aluminium concentrate (for shades RAL 9006, RAL 9007)

Physical properties

Name	Shade	Color index	Density g/cm ³	ONL % weight	VOC g/kg	TOC g/kg
P2013/1800	filler A	-	1.40	70	300	272
P2013/1801	white	PW 6	1.80	80	200	130
P2013/1830	violet	PV 23	1.03	50	500	318
P2013/1841	blue	PB 15:3	1.10	58	420	274
P2013/1859	green	PG 7	1.14	58	420	274
P2013/1867	ochre	PY 42	1.50	72	280	191
P2013/1868	yellow	PY53+PY74	1.33	68	320	210
P2013/1869	yellow lemon	PY 184	2.20	84	160	95
P2013/1878	orange	PO 67	1.12	61	390	258
P2013/1880	russet	PR 101	1.70	80	200	110
P2013/1883	red	PR 254	1.15	63	370	247
P2013/1884	magenta	PR 122	1.05	50	500	350
P2013/1898	black	PB 7	1.09	61	390	209
P2013/1899	black	PB 7	1.16	65	350	198
P2013/1900	filler P	-	1.77	79	210	129
P2013/9110	aluminous	-	1.32	60	400	322

Emission limits

VOC: 0.20 – 0.50 kg/kg of paste	TOC: 0.10 – 0.35 kg/kg of paste
This product is for professional use only. Not for DIY.	

Handling

Read the instructions in the Safety Data Sheet before use and follow all safety instructions and regulations. The product contains organic solvents. Follow basic hygiene rules. Do not eat, drink or smoke while using this product. Avoid contact with eyes, skin or clothing. Wear protective gloves, eye protection, protective clothing. Ensure effective ventilation of the workplace.

Storability

The product keeps the product qualities 24 months from production date in original closed container. To store in dry storage at the temperature 5 to 25 °C. Flammable liquid II. hazard class.

Disposal of packing and waste

Hand over the used, properly empty packing at the collection point of the packing waste. Dispose the packing with the product rest at the place determined by the town for disposal of hazardous waste or hand over to the person authorized for hazardous waste disposal. Further see the product safety data sheet.

These data are only for information and their accuracy is influenced by the properties of individual materials and unpredictable factors during application. The user is responsible for correct use of the product according to the direction for use and for correct application of painting system, i.e. he must always evaluate all conditions of application, which could influence final quality of the top treatment. Therefore we always recommend to the user to carry out the test for actual working conditions and type of surface applied. Above mentioned data are data, which influence individual working conditions and therefore they do not establish a legal claim. It is necessary to consult information outside the terms of this catalogue sheet with the producer.

The producer stipulates the right for the change in the catalogue sheets without previous notification.