

Page number: 01

TELSOL SP 1

Composition	Mixture of organic solvents (hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %) and toluene).
Use	Thinning of synthetic air-drying paints TELKYD and TELKYDUR, applied by spraying.
Density	ca 825 kg/m ³
TOC	0.89 kg/kg
Flammable liquid of I. hazard class (according to ČSN 65 0201).	

TELSOL BR 5

Composition	Xylene (mixture of isomers and ethylbenzene).
Use	Thinning of synthetic air-drying paints TELKYD and TELKYDUR, determined for application by spraying, brush or dipping.
Density	ca 862 kg/m ³
TOC	0.91 kg/kg
Flammable liquid of II. hazard class (according to ČSN 65 0201).	

TELSOL POX

Composition	Mixture of organic solvents (xylene, butyl-acetate, 2-butoxyethanol, butan-1-ol).
Use	Thinning of two-component epoxy paints TELPOX.
Density	ca 854 kg/m ³
TOC	0.75 kg/kg
Flammable liquid of II. hazard class (according to ČSN 65 0201).	

TELSOL PUR 3

Composition	Mixture of organic solvents (2-butoxyethyl acetate, n-butyl acetate and xylene).
Use	Thinning of two-component polyurethane paints TELPUR.
Density	ca 910 kg/m ³
TOC	0,73 kg/kg
Flammable liquid of II. hazard class (according to ČSN 65 0201).	

TELSOL PUR 4

Composition	Mixture of organic solvents (2-methoxy-1-methylethyl acetate, 2-butoxyethyl acetate, n-butyl acetate).
Use	Thinning of two-component polyurethane paints TELPUR.
Density	ca 937 kg/m ³
TOC	0,60 kg/kg
Flammable liquid of II. hazard class (according to ČSN 65 0201).	

TELSOL UNI

Composition	Mixture of organic solvents (xylene and hydrocarbons C9, aromatic).
Use	Thinning of synthetic air-drying and two-component polyurethane paints TELKYD and TELPUR.
Density	ca 880 kg/m ³
TOC	0.89 kg/kg
Flammable liquid of II. hazard class (according to ČSN 65 0201).	

Handling

Read the instructions in the Safety Data Sheet before use and follow all safety instructions and regulations. The product contains organic solvents. Follow basic hygiene rules. Do not eat, drink or smoke while using this product. Avoid contact with eyes, skin or clothing. Wear protective gloves, eye protection, protective clothing. Ensure effective ventilation of the workplace.

Packing

4.0 l; 9.0 l

Storability

The product keeps the product qualities 36 months from production date in original closed container. To store in dry storage at the temperature 5 to 25 °C.

Page number: 02

**Disposal of
packing and waste**

Hand over the used, properly empty packing at the collection point of the packing waste. Dispose the packing with the product rest at the place determined by the town for disposal of hazardous waste or hand over to the person authorized for hazardous waste disposal. Further see the product safety data sheet.

These data are only for information and their accuracy is influenced by the properties of individual materials and unpredictable factors during application. The user is responsible for correct use of the product according to the direction for use and for correct application of painting system, i.e. he must always evaluate all conditions of application, which could influence final quality of the top treatment. Therefore, we always recommend to the user to carry out the test for actual working conditions and type of surface applied. Above mentioned data are data, which influence individual working conditions and therefore they do not establish a legal claim. It is necessary to consult information outside the terms of this catalogue sheet with the producer.

The producer stipulates the right for the change in the catalogue sheets without previous notification.